



PORTABLE ELECTRIC INFRARED HEATERS

HEAVY DUTY METAL SHEATH FHK-SERIES



2.0 KW & 4.5 KW
STAND



6.0KW & 13.5KW
HANDCART

- Double side wall housings to reduce operating temperatures
- 6.0 and 13.5KW heaters have double top baffles to reduce operating temperatures.
- 60° symmetrical heat pattern
- Factory installed U-shaped metal sheath infrared heating elements have an average 5000 hour life
- Heavy duty protective wire screens
- GOLD anodized aluminum internal reflector

UPC 686334	MODEL	KW	BTU's	VOLTS	PH	AMPS	WT.
881739	FHK-224-1A	2.0	6,826	240	1	8.3	17 lbs.
881753	FHK-248-1A			480	1	4.2	
881784	FHK-424-1A	4.5	15,359	240	1	18.8	24 lbs.
881807	FHK-448-1A			480	1	9.4	
882910	FHK-624-3A	6.0	20,478	240	3	14.4	37 lbs.
					1	25.0	
882934	FHK-648-3A			480	3	7.5	
				1	13		
882965	FHK-1324-3A	13.5	46,076	240	3	33.0	65 lbs.
					3	17.0	
882989	FHK-1348-3A			480	1	29.0	

OPTIONAL 25' POWER CORD	
UPC 686334	TYPE
880435	16/3 SO
880435	16/3 SO
880459	12/3 SO
880466	14/3 SO
880497	14/4 SO
880442	10/3 SO
880497	14/4 SO
880466	14/3 SO
880510	8/4 SO
316422	12/4 SO
880527	8/3 SO

Contact Factory for Special Build Models @ 208V, 277V or 600V.

FACTORY PRE-WIRED MODELS WITH 15 ft. CORD & GROUNDED PLUG

UPC 686334	MODEL	TYPE	KW	BTU's	VOLTS	PHASE	AMPS	WT.
881715	FHK-212-1CA	STAND	1.8	6,143	120	1	15.0	18 lbs.
882798	FHK-624-1CA	CART	6.0	20,478	240	1	25.0	40 lbs.

MODEL KW	SQUARE FOOTAGE HEATED				Required Clearance to Combustible Material
	NON-PROTECTED AREA		SEMI-PROTECTED AREA		
	BELOW 35 °F	ABOVE 35 °F	BELOW 35 °F	ABOVE 35 °F	
1.8KW / 2.0KW	25	36	40	50	2 feet
4.5 KW	64	75	90	125	3 feet
6.0KW	85	100	120	150	4 feet
13.5KW	192	225	270	375	7 feet



FHK-624-1CA



FHK-212-1CA

Calefacción Eléctrica, S.A. de C.V.
 Capitán Aguilar No. 529
 Col. Lomas C.P. 64030
 Monterrey, N.L. México
 Conm. (52) 81 83486639
 (52) 81 83488997
 Fax1 (52) 81 83472814
 Fax2 (52) 81 83488944
 Atención al cliente: serv@calelec.com.mx
www.calelec.com.mx

